



TIMPANI

Handheld tympanometer / Screening audiometer



DESCRIPTION

Timpani is a handheld screening tympanometer capable of performing automatic tympanometry exam as well as, optionally licensed, acoustic reflexes test and screening pure tone audiometry.

The device features a wide color display with touchscreen interface.

AVAILABLE TESTS

- Automatic Tympanometry @ 226 Hz (1000 Hz optional)
- Acoustic Ipsi-Reflex Test (optional)
- Automatic Test Sequence (tympanometry + reflex test, optional)
- Screening Pure Tone Audiometry (optional)

MIDDLE EAR ANALYZER SPECIFICATIONS

PROBE TONE

Frequency: 226 Hz
 1000 Hz (optional)
 Level: 85 dB SPL (@ 226 Hz)
 75 dB SPL (@ 1000 Hz)

COMPLIANCE MEASUREMENT SYSTEM

Measurement range: 0.2 ÷ 8.0 ml (@ 226 Hz)
 0.9 ÷ 16.0 mmho (@ 1000 Hz)

TYMPANOMETRY

Meatus compensated viewing mode
 Single scan
 Scan interval (choice): standard, from +200 to -400 a daPa
 reduced, from +100 to -300 daPa
 Safety limits: -750 daPa and +550 daPa
 Scan rate: 400 daPa/sec
 Auto start feature

ACOUSTIC REFLEX TEST

Ipsilateral stimulation, probe tone @ 226Hz
 Pulsed stimulus for reduced artifacts

Exam modes available:

- Automatic threshold
- Fixed intensity

Exam pressure:

- Automatic, between tympanogram peak pressure and peak pressure minus tympanogram width (or ambient pressure, when no peak found)

AVAILABLE STIMULI AND LEVELS

Pure tones: 500Hz, 1000Hz, 2000Hz, 4000Hz
 Attenuator step (selectable): 5 or 10 dB (automatic threshold)
 5 dB (fixed intensity)
 Minimum Intensity: 70 dB HL
 Maximum intensity: 100 dB HL

AUDIOMETER SPECIFICATIONS

AVAILABLE OUTPUTS AND TRANSDUCERS

AC: supra-aural DD45, insert earphones ER-3C*

AVAILABLE STIMULI AND LEVELS

Stimulus: pure tone (see table)
 Attenuator step: 5 dB
 Minimum Intensity: -10 dB HL
 Maximum Intensity and available frequencies:

Frequency (Hz)	AC DD45 (dB HL)	AC ER-3C* (dB HL)
125	60	70
250	80	90
500	90	95
750	100	100
1.000	100	100
1.500	100	100
2.000	100	100
3.000	100	100
4.000	100	100
6.000	90	80
8.000	85	70

*Still supported, but no longer available for purchase.

DEVICE SPECIFICATIONS

OPTIONAL PRINTER

RPP200, wireless thermal printer.
 Paper dimensions: 58mm

CALIBRATION

Validity: 12 months
 All the parameters set through a dedicated software.

COMPUTER INTERFACE

Connection: USB (driverless)
 Compatible software: Inventis Maestro

DISPLAY

Type: Graphical color TFT LCD, capacitive touchscreen
 Size: diagonal 2.8", 43.2 x 57.6 mm
 Resolution: 240 x 320 x RGB

POWER SUPPLY

Internal battery: Lithium-Ion rechargeable battery
 Battery life: more than 4 hours of continuous use
 Main Unit: 5Vdc, 1.4A
 Optional Docking Station: 5Vdc, 1.4A
 External adapter USB dedicated: 100-240 Vac, 50/60 Hz, 0.3-0.15A, responding to IEC 60601-1 standard

MECHANICS

Main Unit:

Size (WxDxH): 65 x 44 x 240 mm / 2.6 x 1.8 x 9.5 in

Weight: 340 g / 12 oz

Docking Station:

Size (WxDxH): 109 x 83 x 131 mm / 4.3 x 3.3 x 5.2 in

Weight: 280 g / 9.9 oz

APPLICABLE STANDARDS

Impedance: IEC 60645-5 Type 2, ANSI S3.39 Type 3

Pure tone audiometry: IEC 60645-1 Type 4, ANSI S3.6 Type 4

Calibration: ISO 389-1, ISO 389-2

Electrical safety: IEC 60601-1 Class II, Type B

EMC: IEC 60601-1-2

CE CERTIFICATE

MDR 2017/745/EU Classification: Class IIa

Classification rule (Annex VIII, 2017/745): 10

Notified body: TÜV SÜD Product Service GmbH (0123)

PRODUCT CODE

11440: Timpani – Handheld tympanometer

INCLUDED PARTS

- Main unit
- Assorted ear tips with cleaning brush
- USB cable
- Medical grade USB power supply
- Carrying case
- User manual

OPTIONAL EXTENSION PACKAGES

- 11504: 1 kHz probe tone license (for tympanometry exam)
- 11505: Reflex license – Basic (Stimuli @ 1 kHz)
- 11506: Reflex license – Plus (Stimuli @ 0.5, 1, 2, 4 kHz)
- 11507: Screening Pure Tone Audiometry (only AC) – without transducers

ACCESSORIES

- 11508: Docking station for Timpani

OPTIONAL PARTS

- 11510: Headset for PTA with Timpani (DD45)
- 10506: Calibration cavities
- 11509: Wireless thermal printer for Timpani
- 11512: Patient response button for PTA with Timpani

DISPOSABLES (with order code)

- 10488: White tips (diam. 6 mm) – Set of 30
- 10489: Pink tips (diam. 7 mm) – Set of 30
- 10490: Violet tips (diam. 8 mm) – Set of 30
- 10491: Green tips (diam. 10 mm) – Set of 30
- 10492: Red tips (diam. 12 mm) – Set of 30
- 10493: Blue tips (diam. 14 mm) – Set of 30
- 10494: Orange tips (diam. 16 mm) – Set of 30
- 10495: Light blue tips (diam. 18 mm) – Set of 30
- 10496: Yellow tips (diam. 21 mm) – Set of 30
- 10511: Box with assorted tips – Set of 160
- 11517: Thermal paper for printer (box of 5 rolls)

- 10554: Cleaning brushes for the tympanometer probe

Timpani is designed by:

INVENTIS S.r.l.

CORSO STATI UNITI, 1/3
35127 PADOVA – ITALY
PHONE: +39.049.8962 844
FAX: +39.049.8966 343
info@inventis.it
www.inventis.it

The Inventis Quality System complies with ISO 13485 standards.ad ap

INVENTIS® is a registered trademark of INVENTIS S.r.l.